

M68V FEATURES & SPECIFICATIONS

STANDARD FEATURES

- True HEPA filter rated 99.97% efficiency @ .3 microns rated for 1100 CFM
- One externally supported 8" diameter by 10' arm with hood
- 1 1/2 HP motor
- 35% eff. pleated prefilter
- Dirty filter gauge
- 3-year limited warranty

OPTIONAL FEATURES

- Motor and fan upgrades including backward inclined fans
- 2000 CFM HEPA
- 65% eff. high capacity pleated prefilter
- Second collection arm
- Minihelic® gauge
- Additional filter modules

DIMENSIONS: 40.25"L x 31"W x 65"H

WEIGHT: 422 lbs. installed
485 lbs. shipping weight

CABINET: 16 gauge welded steel cabinet with ivory enamel finish.

POWER INPUT:

Voltage	Phase	1 1/2 HP Amps
110-120	1	17.2
208-240	1	8.8

MOTOR: Heavy-duty 1 1/2 HP motor with sealed ball bearings.

BLOWER: Belt drive fan capable of 4400 CFM free air, with field adjustable motor sheave.
Factory Set CFM:
One Arm Model: Up to 1100 CFM/ Arm
Two Arm Model: Up to 1000 CFM/ Arm

PREFILTER: 24" x 24" x 4" 35% efficient pleated media.

PRIMARY FILTER: 24" x 24" x 12" HEPA 99.97% certified efficiency @ .3 microns. Rated 1100 CFM.

INSTRUMENTATION: Dirty Filter Gauge – Factory installed pressure gauge designed to determine filter replacement cycle.

SOUND LEVELS: Max 72 dBA at 15 ft., 74 dBA at 9 ft.



The M68V is designed for high efficiency source capture filtration with mobility.



For further information:

BERRIMAN ASSOCIATES
1-800-480-3630
www.berriman.com

Manufacturer has a policy of continuing product improvement, and reserves the right to make changes in design and specification without notice.