

MODEL 625

HEPA/UV Hospital Grade Air Cleaner for Isolation

IN GOES THE BAD AIR...

OUT COMES GOOD AIR.



HEPA-FLOW™ WALL MOUNT APS

When it comes to airborne pathogens, normal protective measures - like surgical masks - offer little protection and ordinary air filtration devices can actually contribute to the problem by becoming breeding grounds.

THE HEPA-FLOW™ WALL MOUNT AIR PURIFICATION SYSTEM (APS)

A COMPLETE SYSTEM OF DEFENSE

Increase **PATIENT SAFETY** and protect yourself and your staff against airborne pathogens with the **HEPA-FLOW™ Wall Mount APS**.

SUPERIOR PERFORMANCE

The **HEPA-FLOW™ Wall Mount APS** has a fully adjustable speed control that can filter up to 575 cubic feet of air per minute, providing a complete exchange and purification of all the air in a typical room 25+ times every hour.

FILTRATION

Unlike other air purifiers, the **HEPA-FLOW™ Wall Mount APS** uses a curved filter design that allows UVC germicidal radiation to bathe the entire filtering surface - maximizing the kill effect and eliminating shadows where pathogens can hide.

HOSPITAL-GRADE HOUSING

The **HEPA-FLOW™ Wall Mount APS** is enclosed in an attractive, durable and easy-to-clean shell that will not dent, scratch or rust. The unit is designed to minimize noise, make efficient use of wall space and reduce risks of injury with rounded edges and corners.

TAMPER-PROOF CONTROLS

Key-secured operation ensures that only authorized staff can set and change critical CFM/negative pressure settings.

FEATURES

- EXCEEDS CDC GUIDELINES
- CLINICALLY ENGINEERED AND DESIGNED
- ECRI & CRA PERFORMANCE TESTED
- TOLL-FREE CUSTOMER SUPPORT
- COMPREHENSIVE USE & CARE GUIDE
- NO-TOOL STANDARD MAINTENANCE
- BLENDS WITH EXISTING DECOR
- FDA REGISTERED, CLASS II MEDICAL DEVICE
- MANUFACTURED UNDER ISO-9001 STANDARDS



Further information:
BERRIMAN ASSOCIATES
1-800-480-3630
www.berriman.com

MODEL 625

HEPA/UV Hospital Grade Air Cleaner for Isolation

HEPA-FLOW™

PORTABLE APS



GENERAL SPECIFICATIONS

FEATURE

PERFORMANCE

Pressurization Capability
Air Changes

Audible Noise
Airflow Direction

DESCRIPTION

Negative, Partial or Full Exhaust
25+ times per hour in 10' x 15' x 9'
ceiling room
≤56dBA @ 3 feet from inlet port
Floor to Ceiling

CONTROL PANEL

Power Switch	Key Operated
Run Timer	Maintenance Meter
Power Indicator	Operating Status
Magnehelic Gauge	Filter Monitor
Mini-Breaker	External Power Reset

ELECTRICAL

Voltage: 115 Vrms @ 60 Hz	Current: 8.3 Amps
Line Cord Supplied	
UL Approved	

CABINET

Material	High-Impact Hospital-Grade Plastic
Locked Access Cover	4 Corners
Plug	Polarized AC

FAN

Airflow	Up to 575 CFM (Cubic Feet/Minute)
Speeds	High, Low (Fully Adjustable)
Power Consumption	1000 Watts
Speed Adjustment	Variable
Lubrication	Permanent

FILTERS

HEPA Filter	99.99% Efficient @ 0.3 Microns
Pre-Filter	30% ASHRAE

UV LIGHT

5 Watts	Continuous Illumination @ 253.7nm
Location	Capture Side of HEPA Filter

INSTALLATION

Floor	Yes- With Locking Casters
Wall	Yes

RECOMMENDED MAINTENANCE

30%ASHRAE Pre-Filter Change	Monthly
HEPA Filter Change	Annually/8000 Hours
UV Light Change	Annually/8000 Hours

OPTIONS

Motion Detector to Automatically Control Fan Speed
Negative Pressure Hood
Pressure Monitoring System
Wall Mounting Brackets

DIMENSIONS

Height: 53"	Depth: 14"	Width: 26 1/4"
Weight: 151 lbs.	Shipping Weight: 194 lbs.	



Further information:
BERRIMAN ASSOCIATES
1-800-480-3630
www.berriman.com